



Dimensioni Flange - Dimensions Flanges EN 1092-2 PN 10									
DNa - DNm	32	40	50	65	80	100	125	150	200
CF	100	110	125	145	160	180	210	240	295
DE	140	150	165	185	200	220	250	285	340
if	19	19	19	19	19	19	19	23	23
zf	4	4	4	4	8	8	8	8	8

Pompa Tipo Pump Size RN	Supporto Bearing Housing	DIMENSIONI - DIMENSIONS [mm]																				Peso Weight [kg]	
		Pompa - Pump					Piedi - Feet					Albero - Shaft											
		DNa	DNm	a	f	h1	h2	b	c	m1	m2	n1	n2	n3	s1	s2	w	d	l	t	u		X ^(a)
32 - 125	32	50	32	80	360	112	140	50	14	100	70	190	140	110	14	14	260	24	50	27	8	100	31
32 - 160	32	50	32	80	360	132	160	50	18	100	70	240	190	110	14	14	260	24	50	27	8	100	38
32 - 200	32	50	32	80	360	160	180	50	18	100	70	240	190	110	14	14	260	24	50	27	8	100	45
40 - 125	32	65	40	80	360	112	140	50	18	100	70	210	160	110	14	14	260	24	50	27	8	100	34
40 - 160	32	65	40	80	360	132	160	50	18	100	70	240	190	110	14	14	260	24	50	27	8	100	40
40 - 200	32	65	40	100	360	160	180	50	18	100	70	265	212	110	14	14	260	24	50	27	8	100	48
40 - 250	32	65	40	100	360	180	225	65	19	125	95	320	250	110	14	14	260	24	50	27	8	100	62
50 - 125	32	65	50	100	360	132	160	50	18	100	70	240	190	110	14	14	260	24	50	27	8	100	44
50 - 160	32	65	50	100	360	160	180	50	18	100	70	265	212	110	14	14	260	24	50	27	8	100	46
50 - 200	32	65	50	100	360	160	200	50	18	100	70	265	212	110	14	14	260	24	50	27	8	100	52
50 - 250	32	65	50	100	360	180	225	65	19	125	95	320	250	110	14	14	260	24	50	27	8	100	64
65 - 125	32	80	65	100	360	160	180	65	19	125	95	280	212	110	14	14	260	24	50	27	8	100	52
65 - 160	32	80	65	100	360	160	200	65	19	125	95	280	212	110	14	14	260	24	50	27	8	100	52
65 - 200	32	80	65	100	360	180	225	65	19	125	95	320	250	110	14	14	260	24	50	27	8	140	60
65 - 250	40	80	65	100	470	200	250	80	23	160	120	360	280	110	18	14	340	32	80	35	10	140	95
65 - 315	40	80	65	125	470	225	280	80	23	160	120	400	315	110	18	14	340	32	80	35	10	140	136
80 - 160	32	100	80	125	360	180	225	65	19	125	95	320	250	110	14	14	260	24	50	27	8	140	63
80 - 200	40	100	80	125	470	180	250	65	19	125	95	345	280	110	14	14	260	24	50	27	8	140	90
80 - 250	40	100	80	125	470	200	280	80	23	160	120	400	315	110	18	14	340	32	80	35	10	140	112
80 - 315	40	100	80	125	470	250	315	80	23	160	120	400	315	110	18	14	340	32	80	35	10	140	139
80 - 400	50	125	80	125	530	280	355	80	16	160	120	435	355	110	18	14	340	42	80	35	10	140	202
100 - 200	40	125	100	125	470	200	280	80	23	160	120	360	280	110	18	14	340	32	80	35	10	140	102
100 - 250	40	125	100	140	470	225	280	80	23	160	120	400	315	110	18	14	340	32	80	35	10	140	121
100 - 315	40	125	100	140	470	250	315	80	16	160	120	400	315	110	18	14	340	32	80	35	10	140	151
100 - 400	50	125	100	140	530	280	355	100	20	200	150	500	400	110	22	14	370	42	110	45	12	140	211
125 - 250	40	150	125	140	470	250	355	80	23	160	120	400	315	110	18	14	340	32	80	35	10	140	140
125 - 315	50	150	125	140	530	280	355	100	20	200	200	500	400	110	22	14	370	42	110	45	12	140	198
125 - 400	50	150	125	140	530	315	400	100	20	200	200	500	400	110	22	14	370	42	110	45	12	140	232
150 - 315	50	200	150	160	530	280	400	100	20	200	200	550	450	110	22	14	370	42	110	45	12	140	213
150 - 400	50	200	150	160	530	315	450	100	20	200	200	550	450	110	22	14	370	42	110	45	12	140	262

Quote e pesi suscettibili di variazione.
 Dimensions and weights are subject to variations.

^(a) Lunghezza del giunto spaziatore.
 Spacer coupling's length.